



标记	DESCRIPTION (描述)	REVISER (修改人)	DATE (日期)
00			2022. 05. 09
01			
02			
03			

PIN: SYMBLE	
1	LEDA
2	LEDK
3	LEDK
4	GND
5	VCI
6	RESET
7	NC
8	NC
9	SDA
10	SCK
11	CS
12	PCLK
13	DE
14	VSYNC
15	HSYNC
16-33	DB0-DB17
34	GND
35	TP_INT
36	TP_SDA
37	TP_SCL
38	TP_RESET
39	TP_VCI
40	GND

3SPI+18RGB

Notes:

1. Unit: mm.
2. Δ Modification rev. number.
3. All radii without dimension R0.3mm.
4. All draft angles to be 1.5°
5. Unspecified Tolerances is :±0.20mm.
6. Driver IC:ST7701S
7. LCD Driver Voltage :3.3±0.3V
8. Color :White
9. Operating Temperature : -20° -- +70° C
10. Storage Temperature : -30° -- +80° C
11. Requirements on Environmental Protection: ROHS HSF

FPC 双面EMI

1.LED电路图:
IF=20mA,VF=19.2V
6C*18=6LED

MAXEN ELECTRONICS LIMITED

	NAME	DATE	Pro.(3):	GENERAL: ±0.2	SIZE: A4
DESIGNED:			UNIT: MM	TOLERANCE: Angle=1°	SCALE: 1:1
CHECKED:			PROJECT NO.	MX-035WR40BFS-N16	SHEET: 1/1
APPROVED:			PART NO.		REV: V00