

标记	DESCRIPTION (描述)	REVISER (修改人)	DATE (日期)
▲	新版发行	FLQ	2022. 05. 09
▲			


PIN	SYMBLE
1	LEDA
2	LEDK
3	LEDK
4	GND
5	VCI
6	RESET
7	NC
8	NC
9	SDA
10	SCK
11	CS
12	PCLK
13	DE
14	VSYNC
15	HSYNC
16	DB0~DB17
34	GND
35	TP_INT
36	TP_SDA
37	TP_SCL
38	TP_RESET
39	TP_VCI
40	GND

TP PIN:

1	GND
2	TP_INT
3	TP_SDA
4	TP_SCL
5	TP_RESET
6	TP_VCI
7	GND

Notes:

1. Display : 4.58" TFT
2. Resolution: 320xRGBx960
3. View Direction: ALL
4. LCD Driver: ST7701S
5. LCM亮度: 300cd/m² (TYP)
6. *:Critical dimension (): Reference dimension;
7. Undefinition Tolerance: ±0.2
8. OPERATING TEMP: -20° C ~ +70° C
9. STORAGE TEMP: -30° C ~ +80° C
10. Requirements on Environmental Protection: ROHS



MAXEN ELECTRONICS LIMITED				SIZE: A4
				SCALE: 1:1
DESIGNED:	NAME	DATE	Pro.(3):	GENERAL : ±0.2
CHECKED:			UNIT: MM	TOLERANCE: Angle=1°
APPROVED:			PROJECT NO.	MX-046HS40FS-N01 SHEET:1/1
			PART NO.	REV: V00