

NOTES:

1. DISPLAY TYPE:TFT
2. OPERATING TEMP: $-20^{\circ}\text{C}\sim 70^{\circ}\text{C}$
3. STORAGE TEMP: $-30^{\circ}\text{C}\sim 80^{\circ}\text{C}$
4. LCD DRIVER: COG(IC:ILI9341);
5. BACKLIGHT: 4 CHIP-WHITE LED
6. GENERAL TOLERANCE: ± 0.20
7. ROHS

CIRCUIT DIAGRAM
(I=60MA V=3.0-3.4V)

MAXEN ELECTRONICS LIMITED			
DRAWN BY:	Luoyan 19/11-14	MX-24NS18-TWZ04	
ME CHECKED BY:	Zouwenyi 19/11-14	DWG Ver: v0.0	UNIT: mm
EE CHECKED BY:	Guoguo 19/11-14	SCALE: 1:1	SHEET NO: 1 OF 1
APPROVED BY:	Zouyixuan 19/11-14		

PIN	SYMBOL
1	GND
2	RESET
3	SCL
4	D/C
5	CS
6	SDA
7	SDO
8	GND
9	VCC
10	LEDA
11	LEDK1
12	LEDK2
13	LEDK3
14	LEDK4
15	XL
16	YU
17	XR
18	YD