


PIN FUCTION	
PIN	SYMBOL
1	GND
2	D0P
3	D0N
4	GND
5	D1P
6	D1N
7	GND
8	CLKP
9	CLKN
10	GND
11	D2P
12	D2N
13	GND
14	D3P
15	D3N
16	GND
17	GND
18	VCC-1V8
19	VCC-1V8
20	NC
21	NC
22	NC
23	NC
24	RSTB
25	NC
26	NC
27	GND
28	K
29	K
30	GND
31	NC
32	GND
33	GND
34	NC
35	A
36	A
37	GND
38	VDD_3V3
39	VDD_3V3
40	NC

NOTES:

- VIEWING DIRECTION : ALL 0° CLOCK
- POLARIZER MODE : TRANSMISSIVE
- OPERATING TEMP : -20°C~+70°C
- STORAGE TEMP : -30°C~+80°C
- DRIVER IC : RM68200
- BACKLIHGT : 12 GHIP WHITE LED SERIES(20mA/LED)
- ROHS COMPLIANCY



Maxen Electronics Limited			VERSION	DESCRIPTION	
			A	依客户图纸设计	2017.02.08
LCM外形图		SCALE:FIT			
PART NO: MX-150HM40-IL04		NO:1/1	UNIT:MM		
		GENERAL TOL: ±0.2			
DRAWN	CHECKED	APPROVED			