





MECHANICAL OUTLINE, UNIT: mm

ELECTRICAL-OPTICAL CHARACTERISTICS

The Ambient temperature Ta = 25°C.

项目	Item	Symbol	Condition	min.	typ.	max.	unit.
外形规格	Appearance specifications	长	Ta = 25°	—	—	—	mm
		宽	Ta = 25°	—	—	—	mm
光辐射均匀性	Luminous Uniformity	亮/暗	If = 100	75	85	—	%
		亮度/对比度	Lr	If = 100	—	—	cd/m²
功耗/漏耗	Power dissipation	P	If = 100	—	—	W	
工作温度	Operating Temperature Range	Toper	normal use	0	—	+60	°C
储存温度	Storage Temperature Range	Tstor	normal use	-20	—	+60	°C

产品平面图

CN2 (PH2.0X14)

PIN	Symbol	Description	note
1	VCC	Power supply voltage +24V	
2	VCC	Power supply voltage +24V	
3	VCC	Power supply voltage +24V	
4	VCC	Power supply voltage +24V	
5	VCC	Power supply voltage +24V	
6	GND	Power ground	
7	GND	Power ground	
8	GND	Power ground	
9	GND	Power ground	
10	GND	Power ground	
11	NC		
12	ON/OFF	Output enable signal	
13	DIM	Dimming signal	
14	PWM	Dimming signal	

MAXEN ELECTRONICS LIMITED

客户型号		产品型号		设计	审核	批准	页码
Cust number:		Product model:		Design:	Check:	Approve:	Sheet:
—		—		—	—	—	2/2

版本 Rev: V10

日期 Date: 2022.07.11

RoHS

一角 Projection:

—

—

—

